Ultrasoft
colours for Luxury & Seamless upholstery

Advanced soft-to-touch fabric

Belmont

Ultrasoft upholstery colours

for Belmont's Luxury and Seamless upholstery specifications

See product images in your preferred colours online at belmontdental.co.uk

Luxury Upholstery

Seamless Upholstery

291-2527 Lagoon

291-0001 White

291-5668 Silver Pearl

291-5666 Dove Grey

291-5708 Granite

291-5806 Schooner

291-4351 Shetland

291-4454 Sonora

291-4460 Parrot

291-4430 Eucalyptus

291-2552 Riviera

291-2553 Cyan

291-2685 Bayou

291-2551 Baltic

291-9385 Plum

291-2556 Admiral

291-3700 Ivory

291-3850 Sand

291-1256 Papryus

291-3779 Taupe

291-3602 Stone

291-5200 Citrus

291-5250 Sassy

291-8243 Apricot

291-8233 Autumn Leaf

291-1347 Poppy

291-1176 Red

291-1312 Chianti

291-3205 Hot Chocolate

291-3666 Fudge

291-5607 Raven Wing

Shown for representative purposes only.

Ultrasoft

Soft-to-touch upholstery fabric synonymous with luxury and durability

GENERAL SPECIFICATIONS

Composition:
100% Polycarbonate Polyurethane Surface
100% Reinforced Rayon Backing
containing TENCEL™ Modal fibers

Weight:
Approx. 9.7 oz. Per Square Yard
Approx. 330 Grams Per Square Metre

Thickness:
Approx. 0.95 Millimetres

Width:
54 Inches / 137 Centimetres

Repeat:
None

PERFORMANCE

Abrasion:
ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 180,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:
14+ Weeks
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating:	ASTM D751
Tear Strength:	ASTM D2261
Breaking Strength:	ASTM D751
Antimicrobial:	ASTM E2180
Tensile Strength:	BS EN ISO 1421

COLORFASTNESS

Light:	AATCC 16.3, 200 Hours, Grade 4 ISO 105 B02, Grade 6
Crocking:	AATCC 8, Grade 4-5 Wet & Dry

FLAMMABILITY REQUIREMENTS

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)
- IMO FTPC Part 8
- BS EN 1021 Parts 1 & 2

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit: **ultrafabricsinc.com**

Made in Japan

Belmont

Perfecting the art of dentistry

For any enquiry, do not hesitate to contact us directly on 020 7515 0333 or visit: **belmontdental.co.uk**